



MASTERSCAN SERIES

HIGH PERFORMANCE DIGITAL ULTRASONIC FLAW DETECTORS



Exceptional near surface resolution

High performance 450 pulser for attenuative materials

Minimum range 0.1mm, maximum 20 metres

Programmable pulser with **ActiveEdge™**

Interface trigger for water path compensation

5 KHz PRF suitable for high speed scanning

THE MASTERSCAN SERIES

Digital flaw detectors that set standards of performance and reliability



For over 20 years the Masterscan name has meant exceptional performance and class leading design, and the 350M and 380M continue this tradition. The latest developments in amplifier and pulser design deliver higher levels of near surface resolution, penetrating power and excellent signal to noise ratio. Typical applications are thin walled components, turbine blades, spot welds, power generation (including EMATs), large castings and forgings.

Unique ActiveEdge™ Transmitter Technology

The Masterscan series has an ActiveEdge transmitter that drives the pulse on both the leading edge and trailing edge. This development enhances near surface resolution, and removes the need for sensitivity reducing damping resistors. The added control achieved by the design helps the Masterscan optimise characteristics for a wide range of transducers, reaching even higher performance.

Robust and Reliable

Sonatest's reputation for robust design and proven reliability is an important aspect of flaw detector ownership. Down time is expensive and should be minimised to ensure maximum productivity. The Masterscan series is constructed to high standards using Xenoy plastics and sealed to IP67, giving excellent water resistance so it can withstand the tough environments in which operators work.

The Masterscan comes with 2 years warranty, extendable to 5 years with Sonacover, and a worldwide service network.



High Performance with Total Control

The 350M and 380M deliver high performance and advanced features, yet our engineers experience in user interface design has ensured it is easy and quick to use. The acknowledged ease of use of previous generation Masterscans has been enhanced with the menu navigation key, providing easy access to functions. The menu structure has been designed to guide the operator through their task with operation quickly becoming second nature.

High Visibility Display

For any flaw detector the display is a crucial element. The Masterscan has a colour transfective TFT display as standard, providing high visibility at any light level. The choice of colours for menus and waveform display enhance clarity, with the LCD simulation mode giving direct sunlight readability. The TFT does not suffer the typical black out problems or temperature limitations of LCD giving full weather capability. The new Full Screen mode maximises the A-scan area to improve readability further whilst testing and its fast response and peak capture functionality ensure any indication is clearly displayed, even if it only appears for one cycle of the 5 KHz PRF.




380M - Systems Integration

The 380M has additional features designed to integrate with automated test systems. The high 5 KHz PRF, interface trigger (IFT) and back wall echo attenuation (BEA) make it an ideal flaw detector for many system applications that require portability or the ability to support manual inspection with the same unit. Proportional and alarms outputs update at the PRF, so high speed testing is easily handled, and the USB interface provides fast set up changes.



SDMS (Optional Sonatest Data Management Software)

This Windows based data management tool allows the user to interface a Sonatest digital flaw detector with a PC. The software provides a frame to upload and download panel settings and A-scans. These can also be copied and pasted into Word for customised reporting. Thickness readings can be transferred directly into Excel with the ability to produce charts for B & C-Scans, colour 3D mapping etc.



MASTERSCAN SERIES Specifications 350M and 380M

Test Range	0 - 1mm (0.05in) up to 0 - 20000 mm (800 in.) at steel velocity. Variable in 1,2,5 sequence or continuously in 1mm (0.05in) increments. Also from 1 to 5000(µs).	DAC	Maximum of 10 points may be entered and digitally drawn to construct a DAC curve. Reference, -6dB, -12/14dB curves may be selected for JIS/ASME codes or Reference, -2dB, -6dB, -10dB for EN 1714.
Velocity	256 to 16000m/s continuously variable.	TCG	Time Corrected Gain, also known as Swept Gain. 40dB dynamic range greater than 30dB per microsecond and up to 10 points may be used, setting all signals initially to 80% FSH.
Probe Zero	0 to 999.999 µs, continuously variable.	Backwall Echo Attenuation	0- 40dB attenuation.
Delay	Calibrated delay from 0 -10000mm in 0.05 mm steps at steel velocity (0-400in. in 0.002 in. steps).	AWS	Built in software for evaluation of defect indications in accordance with AWS D1.1 structural weld code.
Gain	0 to 110dB. Adjustable in 0.5, 2, 6, 10, 14 and 20dB steps. Direct access to gain control at all times.	AVG/DGS	Automatic calculation from probe data, up to 10 probes stored.
Test Modes	Pulse echo and transmit/receive.	API	Flaw sizing complying with API 5UE
Pulsar	100V - 300V (450V MS380) square wave pulser. Pulse width from Spike to 2000ns duration - 200V peak amplitude with rise/fall times <5ns into 50 ohms: Width adjustable in 2% of nominal width, minimum 1ns maximum 40ns.	Auto-Cal	Provides automatic calibration from two echoes.
Damping	Selectable between 33, 50, 100 & 400 ohms.	Clock	Sets time and date.
P.R.F	Selectable 35 to 6000 Hz in 5 Hz steps.	Reference Waveform	This menu displays a waveform from one of the A-log stores as a reference or fingerprint display in a colour different from the active display highlighting differences from the reference.
Update Rate	60Hz (NTSC Mode); 50Hz (PAL Mode).	Notes	Alphanumeric labelling for panel and A-log allows the user to enter Notes for storage with panel settings and A-scans.
Rectification	Full wave, positive or negative halfwave and unrectified rf.	Display Freeze	For capturing the current A-scan image.
Frequency Range	6 narrow bands centred at 0.5 MHz, 1MHz, 2.25MHz, 5MHz, 10MHz and 15MHz. Broad band at 2 MHz to 22MHz (-6dB) and 1MHz to 35 MHz (-20dB).	Peak Memory	For echodynamic pattern determination.
System Linearity	Vertical = 1% Full Screen Height (FSH). Amplifier Accuracy ± 0.1dB. Horizontal ±0.4% Full Screen Width (FSW).	Keylock	Prevents accidental alteration of parameters.
Reject	80% linear reject. LED warning light when selected.	Help Key	For instant operator guidance on using the Masterscan Series.
Units	Metric (mm), inch (in) or time (µs).	Language Support	Supports multiple languages, user selectable. English, German, Spanish, French, Dutch. Others available on request.
Display	Colour Transfective TFT: Display area 103 x 77 mm (4.05 x 3.03in) 320 x 240 pixels. A-Scan Area 300 x 200 pixels, 8 colour options and variable brightness.	Waveform Smoothing	Gives a smooth signal envelope, simulating analogue equipment.
Gate Monitor	Two fully independent gates for echo monitoring and thickness measurement. Start and width adjustable over full range of unit, amplitude variable from 0 to 100% FSH. Bar presentation. Positive or negative triggering for each gate with audible and visual alarms.	Outputs	Full bi-directional serial interface to transfer parameters, thickness readings and waveform memories. Composite video, PAL or NTSC compatibility. Analogue proportional outputs programmable to distance or amplitude of signal in the gate.
Gate Expansion	Expands range to width of Gate 1.	Front USB	For connection to printers, keyboards and PC.
Gate Monitor Delay	Selectable 0.6 seconds delay on gate 2 negative monitor tracking.	Printers	Supports Hp Deskjet, Epson, Cannon.
Measurement Modes		Power	Lithium Ion battery pack 14.4V, 5.0 ampere hours, gives up to 11 hours duration from a fully charged pack. Indication of low battery status. Recharge time 3-4 hrs.
Mode 1	Signal Monitor	Additional 380M Features	
Mode 2	Depth and amplitude of first signal in gate.	Interface Trigger	Interface gate locks to surface echo and eliminates water path variation.
Mode 3	Echo-to-Echo distance measurement. (single gate)	High Power Pulsar	As 350M, plus -450 Volt peak voltage.
Mode 4	Trigonometric display of beam path, surface distance and depth of indication, curve surface correction and X-OFFSET for probe index. Half skip indication on screen.	Charger	100 - 240 VAC, 50-60 Hz.
Mode 5	Gate to Gate distance measurement. (independent gates).	Transducer Sockets	BNC or LEMO (factory option)
Mode 6	T-Min mode for holding minimum thickness reading. Resolution to 0.01mm (0.001in) for distance measurement or 1% FSH for amplitude measurement. Large display of measurement at top of A-Scan display. Measurement mode selectable between peak and flank.	Environmental	Case sealed to IP67
A-Scan Memory	Maximum of 800 waveforms can be printed or transferred to a PC via RS232 serial interface using optional SDMS software.	Temperature	Operating -10°C to +55°C (14 to 131°F). -20°C to +70°C. (-4 to 158°F) survivable. Storage: -40° to +75°C. (-40 to = 167°F)
Panel Memory	100 stores for retaining calibrations.	Size	255 x 145 x 145mm (10.0 x 5.7 x 5.7 in)
Thickness Logging	Storage for 8000 thickness readings configured either by Block/Location/Number mode or pre-programmable work sheets in sequential mode. Readings can be exported to MS Excel using optional SDMS software.	Weight	2.5kg (5.5lbs) with Li-Ion cells.
AGC	Automatic Gain Control automatically sets the signal to a level between 10-90% FSH with tolerance between 5-20% accuracy.	Standard Kit Includes	Masterscan 350M or 380M Li-ion Battery & Battery Charger Fabric Carry Bag Calibration Certificate Instruction Manual (EN12668)

SONATEST LTD

Dickens Road, Old Wolverton
Milton Keynes, MK12 5QQ, UK.
Tel: +44 (0)1908 316345
Fax: +44 (0)1908 321323
www.sonatest.com
sales@sonatest.com

Distributed by:

ATG s.r.o.
Matejska 2416
16000 Praha6
www.atg.cz

